



# BERGER PRODUCT SPECIFICATIONS

## APEX DURACAST PEBBLE TEX

Textured Coating

### PRODUCT DESCRIPTION

A pure acrylic polymer based emulsion coating specially formulated to provide an attractive textured architectural finish.

- Very tough and highly durable.
- Excellent adhesion properties.
- Able to achieve a variety of fine to coarse textured finishes.
- Can be topcoated with conventional water-based and solvent-based topcoats.
- Suitable for use on both interior and exterior surfaces.

### DESIGN USE

- As a texture coat for both interior and exterior masonry substrates.

### PHYSICAL DATA

<b>WEIGHT SOLIDS</b>	84 ± 3%
<b>SPECIFIC GRAVITY</b>	1.75 ± 0.05 g/cm <sup>3</sup>
<b>DRY FILM THICKNESS (DFT)</b>	NA
<b>WET FILM THICKNESS (WFT)</b>	NA
<b>NUMBER OF COATS</b>	1
<b>THEORETICAL COVERAGE</b>	1.0 – 1.5 m <sup>2</sup> /litre, depending on size of texture desired.
<b>COLOUR RANGE</b>	White
<b>NO. OF COMPONENTS</b>	One
<b>STANDARD PACKING SIZE</b>	30 Kgs

### APPLICATION METHOD

Conventional Air Spray

This is the recommended method of application

Tip Size : 1.5 – 5.0 mm (depending on size of texture desired)

Pressure : 2.5 – 4.5 kg/m<sup>2</sup>

The tip size and air pressure should be adjusted / varied to obtain the desired texture size and pattern.

### DRYING TIME

Ambient Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
15 °C	4 hours	16 hours	24 hours	Indefinite
25 °C	2 hours	8 hours	12 hours	Indefinite
35 °C	1 hour	4 hours	6 hours	Indefinite

### ADDITIONAL INFORMATION

Thinner	Not required.
Thinning Ratio	2% maximum if required
Cleaning Solvent	Water
Flash Point	N.A.
Storage Requirements	Store in a cool, dry area away from direct sunlight.



# BERGER PRODUCT SPECIFICATIONS

## APEX DURACAST PEBBLE TEX

Textured Coating

### SURFACE PREPARATION

The service life span and the service performance of this product are directly related to the degree of surface preparation.

- New concrete should be left for at least 21 days to cure before coating.
- The moisture content of the concrete surface should be checked and ensured to be below 6% when measured with a reliable moisture meter, such as the Sovereign Moisture Meter.
- The surface to be coated must be clean and free from all loose extraneous materials such as loose paint, dust etc.
- If fungus or algae is present, first treat with Berger Fungicidal Wash and leave for 24 hours. Then, thoroughly rinse and wash or scrape away all the fungus.
- If grease is present, clean using a mild detergent or solvent and rinse thoroughly to ensure complete removal of the grease, detergent and solvent.
- Apply a suitable sealer coat such as Berger Plastaseal / Berger Water-Based Sealer prior to application of this product.
- For overcoating over old coatings, a high pressure water cleaning should be performed to remove all loose or flaking coatings and ensure the remaining coatings are tightly adherent.

### PRODUCT USE RESTRICTIONS

- Not recommended for direct application onto bare concrete / plastered surfaces. A suitable primer should be applied first.
- Actual pattern of texture will depend on tip size, spray pressure and dilution factors.

### SAFETY PRECAUTION

Avoid contact with eyes and skin. Wear suitable protective clothing.

Ensure that there is adequate ventilation in the area where the product is being applied.

In case of fire, blanket flames with foam, carbon dioxide or dry chemicals.

### FIRST AID

- Eyes** : In the event of accidental splashes, flush eyes with warm water immediately and seek medical advice.
- Skin** : Wash skin thoroughly with soap and water or approved industrial cleaner. Do Not Use solvents or thinners.
- Inhalation** : Remove to fresh air, loosen collar and keep patient rested.
- Ingestion** : In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

For further safety information, please refer to our **Material Safety Data Sheet (MSDS)**

### DISCLAIMER

*The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.*