



BERGER PRODUCT SPECIFICATIONS

BERGER GLOSS 7

Alkyd Gloss Finish

PRODUCT DESCRIPTION

A solvent-based quality alkyd coating formulated with weather resistant inert pigments that provides an attractive and durable high gloss finish.

- Good outdoor durability and colour retention properties.
- Excellent adhesion to ferrous surfaces, wood and aged coatings.
- Suitable for application as a finish coat for masonry substrates.
- Easy application by brush or roller.
- High opacity / covering ability.
- Lead free.
- Washable and able to clean to keep away from dirt pickup.
- Certified for compliance to SS7 by TUV SUD PSB Pte Ltd.

DESIGN USE

- As a finish coat for both interior and exterior ferrous surfaces, masonry substrates, wood and timber products etc.
- As a maintenance coating over aged coatings.

PHYSICAL DATA

VOLUME SOLIDS	50%
DRY FILM THICKNESS (DFT)	25 – 35 µm per coat
WET FILM THICKNESS (WFT)	50 – 70 µm per coat
NUMBER OF COATS	2
THEORETICAL COVERAGE	20.0 m ² /litre per coat @ 25 µm dft
FINISH	High Gloss
COLOUR RANGE	Wide range available. (Please refer to our colour fan deck)
NO. OF COMPONENTS	One
STANDARD PACKING SIZE	5 Litres

APPLICATION METHOD

Brush, Roller or Conventional Air Spray These are the recommended methods of application.

Stir contents of the can thoroughly before use. Thinning is not usually required. However, if thinning is desired, do not exceed the recommended thinning ratio.

Do not apply this product if the relative humidity exceeds 85% or if the substrate temperature is within 3°C of the dew point.

DRYING TIME

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
15 °C	12 hours	24 hours	16 hours	Indefinite
25 °C	6 hours	16 hours	12 hours	Indefinite
35 °C	3 hours	12 hours	6 hours	Indefinite

ADDITIONAL INFORMATION

Thinner	Solvalux 7-9
Thinning Ratio	5% maximum
Cleaning Solvent	Solvalux 7-9
Flash Point	> 38°C
Storage Requirements	Store in a cool, dry area away from direct sunlight.



BERGER GLOSS 7

Alkyd Gloss Finish

SURFACE PREPARATION

The service life span and the service performance of this product are directly related to the degree of surface preparation.

- This coating is designed to be applied over an alkyd primer / undercoat, e.g. Berger Luxaprime 1250 / Berger Undercoat.
- The surface to be overcoated should be dry, free from surface contaminants, sound and undamaged.
- Soluble salts must be removed by washing with fresh water. Dry brushing should be done to remove dirt and dust. If grease is present, clean using a mild detergent or solvent and rinse thoroughly.
- All loose and flaking coatings should be removed and taken back to a firm edge.
- Ferrous surfaces should be primed with Berger Luxaprime 1250, Luxaprime 1000 or other suitable primer. A build coat of Berger Undercoat is recommended prior to application of this product.
- Berger Aluminium Wood Primer should be used to prime wooden substrates. A build coat of Berger Undercoat is recommended prior to application of this product.
- Ensure that the minimum overcoating interval of the primer / build coat has been exceeded prior to application of this product.

PRODUCT USE RESTRICTIONS

- This product is not suitable for exposure to acids, alkalis, solvents and oils.
- This product is not suitable for immersed conditions.
- This product is not recommended to wash by chemicals, detergents and jet washing.

SAFETY PRECAUTIONS

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, gloves and goggles. Use a dust mask if applying by spray.

Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge. In case of fire, blanket flames with foam, carbon dioxide or dry chemicals.

FIRST AID

- Eyes** : In the event of accidental splashes, flush eyes with warm water immediately and seek medical advice.
- Skin** : Wash skin thoroughly with soap and water or approved industrial cleaner. Do Not Use solvents or thinners.
- Inhalation** : Remove to fresh air, loosen collar and keep patient rested.
- Ingestion** : In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

For further safety information, please refer to our **Material Safety Data Sheet (MSDS)**

DISCLAIMER

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.